

## Screenzone Recessed Air Curtains - RAC0603, RAC0604, RAC1006, RAC1306, RAC1309, RAC1509 & RAC1512

## 3kW, 4.5kW, 6kW, 9kW & 12kW

Designed to fit above a doorway in a suspended ceiling, the Recessed Screenzone provides a discreet welcoming curtain of warmth for doorways in shops, hotels, offices and commercial premises. Overall energy savings are likely when the heater is sited above a frequently opened external door as the airstream can prevent heat loss.

- 3kW, 4.5kW, 6kW, 9kW or 12kW rating
- · Choice of single phase or 3 phase models
- Will fit a recess as shallow as 210mm (155mm unit depth plus 55mm free air)
- Supplied with remote switch
- 3 heat settings
- Fan only setting for air circulation
- Automatic safety cut-out for thermal overload protection
- Supplied with white grille





- For single phase models

- For single or 3 phase models

## Dimensions (mm) & Weight (kg):

Model No.	Depth	Width	Length	Weight
RAC0603 / RAC0604	155	339	634	9.5
RAC1006	155	339	985	13.5
RAC1306 / RAC1309	155	339	1350	20.0
RAC1509 / RAC1512	155	339	1550	23.0

Model No.	kW	Max Mounting Height (m)	dBA	Single	Single or 3 Phase
RAC0603	3	2.8	55	•	
RAC0604	4.5	2.8	55	•	
RAC1006	6	2.8	57	•	
RAC1306	6	2.8	60		•
RAC1309	9	3.4	60		•
RAC1509	12	3.4	62		•
RAC1512	12	3.4	62		•

Note: dBA readings are taken at 3 meters from the heater in a free field environment.