

## **Recessed Ceiling Fan Heaters - Wireless Controlled**

Recessed ceiling heaters are designed for discreet positioning in a suspended 600mm standard ceiling panel. They are ideal to heat areas where wall and floor space is at a premium such as shops and offices.

- 3kW, 4.5kW or 6kW rating
- All RX and SL heaters are compatible with advanced single zone controllers\*
- Run-back time controllers\*\* are compatible with SL heaters only
- Fits standard 600mm modular suspended ceiling system
- · Sealed heater box for improved energy efficiency
- Will fit shallow 210mm recess
- Light weight for easy installation
- Quiet operation
- Automatic safety cut-out
- Fan only setting for air circulation (for RX models)
- LED indicator light
- Complete with white aluminum diffuser

## \* Advanced single zone controllers: CRXSL, SLTI and LC controllers

\*\* Run-back time control and thermostat: SLPB, SLVT, SLVTB, SLPIR and SLPBWP controllers

## Dimensions (mm) & Weight (kg):

Model No.	Rating (kW)	Depth	Width	Length	Weight	dBA	Optimum Ceiling Height (m)
HE7230SL / HE7230RX	3	175	595	595	7.5	37	3.0
HE7245SL / HE7245RX	4.5	175	595	595	7.5	38	3.3
HE7260SL / HE7260RX	6	175	595	595	10.5	40	3.6

