

BFH2SL & BFH2SLSS Downflow Fan Heaters - Metal Bodied

These are ideal for bathrooms, kitchens and areas requiring localised, controllable heat. The BFH2SL(SS) Heatflow features heating control options with compatible wireless controllers, comfort and setback temperature settings and automatic overheat safety cut-out. For ease of installation, it is fitted with a 0.9m cable.

- 2kW rating
- Compatible with advanced single zone controllers* and run-back time controllers**
- One controller can operate multiple SL heaters
- Automatic safety cut-out
- LED indicator light
- Fitted power supply cable
- Fixing/Securing bracket
- Metal bodied
- Finished in white or stainless steel



* Advanced single zone controllers: CRXSL, SLTI and LC controllers

** Run-back time control and thermostat: SLPB, SLVT, SLVTB, SLPBWP controllers

Dimensions (mm) & Weight (kg):

| Model No. | Rating (kW) | Height | Depth | Width | Weight | Finish |
|-----------|-------------|--------|-------|-------|--------|-----------------|
| BFH2SL | 2 | 200 | 110 | 300 | 2.0 | White |
| BFH2SLSS | 2 | 200 | 110 | 300 | 2.0 | Stainless steel |

Note: 'SS' denotes Stainless Steel model.