

## Sunzone Radiant Heaters - Wireless Controlled

A metal sheathed element adds to their robust construction and makes them the ideal choice for a variety of installations. Sunzone can be wall, ceiling or trunking mounted and each unit is supplied with a pair of metal brackets which provide angular adjustment for directional radiant heat. It is recommended these units be installed via a Residual Current Circuit Breaker.

- 2kW or 3kW rating
- Compatible with advanced single zone controllers\* and run-back time controllers\*\*
- One controller can operate multiple SL heaters
- Highly efficient, corrosion resistant aluminium reflector
- Directional radiant heat
- Supplied with 1m of high temperature cable
- Finished in barley white with chrome guard



\* Advanced single zone controllers: CRXSL, SLTI and LC controllers

\*\* Run-back time control and thermostat: SLPB, SLVT, SLVTB, SLPIR and SLPBWP controllers

### Dimensions (mm) & Weight (kg):

Model No.	Rating (kW)	Height	Depth	Width	Weight
HE6502SL	2	86	56	1310	1.8
HE6503SL	3	86	56	1720	2.6

Note: 100mm clearance from adjacent wall or ceiling required.

Model No.	Optimum Mounting Height Wall Mount/Suspended
HE6502SL	2.1m Min 3.0m Max
HE6503SL	2.1m Min 3.7m Max