

RESIDENTIAL COMMERCIAL



PORTABLE

PORTABLE AIR-CONDITIONING UNIT



R290



**SIMPLE AND EASY TO MOVE
THANKS TO ITS FOUR WHEELS
AND HANDLES**



**HIGHLY FLEXIBLE
PLUG-AND-PLAY SOLUTION**



**INTEGRATED CONDENSATE
DRAIN SYSTEM**



**ENVIRONMENTALLY RESPONSIBLE
WITH REFRIGERANT HC R290**





TECHNICAL CHARACTERISTICS

PARTS
3 YEARS
WARRANTY

COMPRESSORS
5 YEARS
WARRANTY



PORTABLE AIR-CONDITIONING UNIT

UNIT		51CPD09FS7	51CPD10FS7	51CPD12FS7
Cooling capacity	kW	2.6	2.9	3.5
EER	W/W	2.6	3.1	2.6
Energy Efficiency Class		A	A+	A
Airflow	m ³ /h	345	380	380
Sound power level (Hi)	dB(A)	65	65	65
Sound pressure level (Hi/Mi/Lo)	dB(A)	50.9/49.8/49.3	53.1/51.8/51.7	53.7/52.0/51.9
Refrigerant amount	kg	0.2	0.2	0.22
Temperature range	°C	17-35	17-35	17-35
Room surface area (Cooling Standard)	m ²	12-18	13-20	16-23
Weight	Kg	29.5	32	34
Dimension (W*D*H)	mm	454x365x700	467x397x765	467x397x765
Power supply	Ph-V-Hz	1Ph. 220-240V~. 50Hz	1Ph. 220-240V~. 50Hz	1Ph. 220-240V~. 50Hz

KEY FEATURES

- Follow me function, for airflow control.
- Washable filter.
- Wireless remote control.

CONTROLS



Wireless remote control
(supplied as standard)



www.ciat.uk.com